



Block Heaters

Block heaters, digital, SBH:D

- Choice of 130°C or 200°C maximum temperature
- Digital setting and display
- Uniform and stable temperatures

Construction similar to the SBH130. The bright, easy to read LED display facilitates very easy setting of the required temperature and also accurate monitoring of the actual temperature. Excellent temperature stability and uniformity is maintained via sensitive electronic controls. Heats to 100°C in less than 12 minutes.

Technical Specification

| | SBH130D | SBH200D |
|----------------------------------|--------------------------|--------------------------|
| Number of blocks | 2 | 2 |
| Temperature range | Ambient +8°C to 130°C | Ambient +8°C to 200°C |
| Temp. stability at 37°C | ±0.1°C | ±0.1°C |
| Uniformity within block at 37°C | ±0.1°C | ±0.1°C |
| Uniformity within block at 130°C | ±1°C | ±1°C |
| Display resolution | 0.1°C | 0.1°C |
| Dimensions, mm (w x d x h) | 235 x 280 x 115 | 235 x 280 x 115 |
| Net weight, kg (without blocks) | 2.3 | 2.3 |
| Heater power | 300W | 300W |
| Electrical supply | 230V, 50Hz | 230V, 50Hz |
| IP Rating | 31 | 31 |

Ordering Information

| Model | Description |
|---------|---------------------------------------|
| SBH130D | Block heater, 2 block, digital, 130°C |
| SBH200D | Block heater, 2 block, digital, 200°C |

All models supplied complete with block extraction tool but without aluminium blocks which must be ordered separately. A wide range of blocks is available, see page 6 for details.



SBH130D



SBH130D showing block extraction tool (included)